



Orange Proofer

The IGT Orange Proofer for offset inks is an ideal low cost and efficient method of checking the colour of offset inks. It can be used on a variety of substrates including paper, board, plastic, film, cellophane, laminate, metals etc.

Applications

The IGT Orange Proofer:

- makes colour strips of offset inks with a known ink layer thickness
- gives a high degree of simulation to on-press performance for print quality mottle and set-off
- is specifically designed for computerised colour measuring, spectrophotometers, colour matching systems and visual appraisal
- takes density measurements including establishing colour density tolerances and determination of coverage, wear resistance, scratch resistance, flexibility, adhesion and gloss, ink transfer (g/m^2), light fastness and resistance to chemicals
- is used in the printing ink, paper and board, print, metal, plastics and packaging, resin, lacquer, coatings and raw materials industries

Features

- Inking and printing on a single application
- Reliable, repeatable and reproducible results
- Inking unit with two aluminium drums and top roller for conventional inks
- Complies with CE standards

Operation

The IGT Orange Proofer consists of an inking section and a printing unit. Ink is applied to the top roller of the inking section and distributed within 30 seconds. The printing disc is then positioned on the top roller and, after 15 seconds of inking-in, is placed on the printing shaft. The test material is attached to the substrate carrier and placed underneath the shaft of the printing disc. The print is made automatically after the printing force has been applied.



TENDRING *pacific*

Norfolk House, Great Chesterford Court, Great Chesterford, Essex CB10 1PF

T: (44) 0870 240 1886 F: (44) 0870 240 1887

E: sales@tendringpacific.com

www.tendringpacific.com

Orange Proofer

Technical data

Inking section

Two aluminium drums with top roller

One aluminium drum driven

Top roller – elastomer for conventional inks
rubber for UV-curing inks

Short inking time: inking 30 s and printing disc 15 s

Easy to clean

Printing section

Printing speed 0.3 m/s

Printing force 100–800 N

Printing length 200 mm

Printing width 50 mm

Maximum substrate thickness 4 mm

Independent drive

Discs – printing width 35, 50 mm

Range of discs available:

- for UV inks, disc with rubber or a rubber blanket
- for conventional inks, disc with coated rubber or a rubber blanket

Physical specifications

Weight 25 kg

Dimensions 620 × 350 × 320 mm (W × D × H)

Power requirements

115/230 V, 50/60 Hz

Option

The IGT ink pipette is recommended for applying ink to the top roller. This significantly increases the accuracy of the ink application and the results of the tests. The IGT ink pipette HR is available for even greater accuracy.



Applying ink with the IGT ink pipette



Inking the printing disc



TENDRING *pacific*

Norfolk House, Great Chesterford Court, Great Chesterford, Essex CB10 1PF

T: (44) 0870 240 1886 F: (44) 0870 240 1887

E: sales@tendringpacific.com

www.tendringpacific.com